



EXTENDS THE VASE LIFE OF YOUR ROSES

SPRAY-MASTER SELECTION FOR ROSES

The SPRAY-MASTER SELECTION is the ideal solution for the mechanical sorting for length of your Roses combined with the application of LIQUIDSEAL

The design principle of the machine combined with the chosen technology is highly suitable for deployment in areas where service is limited. Your own Maintenance Staff fully capable of providing all required service on by themselves. To achieve this we chose for simplicity of design and durability of all components. Maintenance of all moving parts has been kept very simple. Even the technically more advanced components of the system can be serviced by your own department due to the modular design and construction.



PRINCIPE

Operation is easy, 6 persons can fill the machine to capacity during operation. At a maximal speed of 2-3 roses per second these are accurately and efficiently coated with LIQUIDSEAL. After treatment roses are selected for length and ejected at one of the 7 possible stations into a buffer. The selection system can easily simply be adjusted manually for different length requirements by moving of sensors.

The advantage of the integrated SPRAY-MASTER is that all excess LIQUIDSEAL is efficiently collected for recycling and any mist is effectively ventilated.

CONSTRUCTION


The machine is largely constructed from coated steel using mechanical components which require little or no maintenance. For detailed information on the SPRAY-MASTER we refer to our SPRAY-MASTER brochure. have designed the SPRAY-Master in such a manner that it may be exchanged within minutes for a replacement unit which is held at the ready for your call with is. This is possible both with direct- as well as with lease-purchase.



TECHNICAL DETAILS SPRAY-MASTER SELECTION:

Supply Voltage	230V 50Hz
Supply Capacity	2,5 kW max
Air connection	6 bar
Compressed air use	200 l / min
Positions for hanging	6
Roses	
Selection	7 lengths
Emissions positions	7-25
roses	
Speed Carousel	8000 per hour
Stem length	300-1000mm
Dimensions Spray-master	700x500x1200
Dimensions carrousel	8300 x 1450 x 1750
Total weight	about 1100kg
Ventilation	500 m3 / hour
Diameter ventilation ducting	160mm, not supplied
Roof ducting	not supplied




 Research & advice




 Design



 Assembly



 Installation & Services